

The Dust-Free Glass Kiln that is so much more ...





Chameleon

The **Chameleon** glass & hobby kiln is the new home kiln for glass artists and other fired arts enthusiasts. It will fire low-fire ceramics, PMC and do heat treating as well as glass fusing. It is the first small square kiln for home use on the market with L&L's unique and famous hard ceramic element holders. Complete easy-to-follow visual instructions make this kiln ideal for the beginner yet powerful enough for experienced users.



Element Support Element Terminations Elements Thermocouple **Element Shut Off** Integrated Stand **Corrosion Resistant Case Handles** Sloping Control Panel **Automatic Programme Control Included Programs Programming** No of Segments in Each Programme **Complete Instructions** On/Off Switch/Circuit Breaker **Power Cord** Sides & Bottom Insulation Top Insulation Lid Seal **View Port Three Year Warranty**

Hard Ceramic Element Holders on top - no dusting Stainless Bolts , no special tools to change One Element mounted in lid Heavy-duty 8 gauge type K Door Switch shuts off all power to element Integrated Stand is part of the control panel All Corrosion resistant aluminized metal & stainless steel Four handles are included for easy lifting Sloping Control Panel makes it easy to see controls Bartlett Programme Control Four user-defined programs Programs stay in memory until changed Eight (each segment has a ramp, set point and hold) Complete easy-to-read manual Circuit Breaker/Switch turns off all power to kiln Included 6.4 cm of Insulating Firebrick 7.6 cm of Insulating Firebrick Lid is routed around perimeter for excellent heat seal 2.5 cm Diameter View Port in Front

Three Year Limited Warranty



SPECIFICATIONS

| Model Number | Model CH12-9 |
|------------------------------|--|
| Interior Size | 34.3 cm (13-1/2") Square by 22.9 cm (9") High |
| Volume | 26.6 liters (0.94 cubic feet) |
| Exterior Size | 48 cm (19") Wide by 55 cm (21-1/2") Deep by 51 cm (20") High |
| Watts & Amperage | 2850 watts, 13 Amps (at 220 volts) |
| Volts & Phase | 220-240 Volts, 1 phase |
| Weight | 54.3 Kg (120 pounds) |
| Shipping Weight & Dimensions | 72.6 Kg (160 pounds), 94 cm (37") Square by 86cm (34") High |
| Temperature Limit | 1100°C (2200°F) |

All transactions are subject to our Terms and Conditions of Trading